



**SPECIFICATIONS:**

**PSI/Temperature Rating:** 300 PSI / 250° F  
**Body Material:** Bronze ASTM B584  
**End Connections:** Female NPT  
**Body Tappings:** 1/4" NPT  
**Strainer:** 20 mesh stainless steel  
**Ball Valve:** Brass body with chrome plated brass ball, 600 WOG  
**Assembly:** Strainer comes fully assembled  
**Body Tappings<sup>1</sup>:** Combination P/T Test Valve and Manual Air Vent (CPTA) and Drain Valve (not pictured)

**DIMENSIONS & WEIGHTS (NOMINAL)**

SIZE	MODEL NO.	A LENGTH	B HEIGHT	WEIGHT (LBS.)
1/2"	3650D	4.7	4.0	1.5
3/4"	3650F	5.5	4.2	2.3
1"	3650H	6.5	5.0	3.3
1-1/4"	3650J	7.5	5.7	4.9
1-1/2"	3650K	8.5	6.5	5.4
2"	3650L	10.2	7.5	8.7

**MODEL NUMBER SELECTION**

Insert D=1/2", F=3/4", H=1"  
 J=1-1/4", K=1-1/2", L=2"

Add an "X" for Y-Strainer only, no Ball valve

3
6
5
0
B

---



---

<sup>1</sup> Body Tappings for accessories are a leak proof metal to metal seal and do not require pipe dope or tape. Tape or dope should not be used.

Replaces form F-2233F

This specification © 2015 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606  
 (949) 559-6000 Fax (949) 559-6088  
 www.GriswoldControls.com

6/15  
 F-2233H

