

**Flow Control Cartridge Code
Quick Reference Guide**



**1/2" Space Saver Cartridge
2-32 PSID**

Cup	Spring	GPM	4-57 PSID		
			Cup	Spring	GPM
-12	2=	0.25			
-13	2=	0.33			
-01	2=	0.50	-501	4=	0.50
-03	2=	1.00	-502	4=	1.00
-05	2=	1.50	-503	4=	1.50
-07	2=	2.00	-504	4=	2.00
-09	2=	2.50	-505	4=	2.50
-11	2=	3.00	-506	4=	3.00

3/4" Standard Cartridge

1-14 PSID

Cup	Spring	GPM
(1.1) 11-	1=	0.33
01-	1=	0.50
02-	1=	0.67
03-	1=	1.00
04-	1=	1.33
05-	1=	1.67
06-	1=	2.00
07-	1=	2.33
08-	1=	2.67
10-	1=	3.33
12-	1=	4.00
14-	1=	4.67
16-	1=	5.00

2-32 PSID

Cup	Spring	GPM
(1.1) 11-	2=	0.55
01-	2=	0.75
02-	2=	1.00
03-	2=	1.50
04-	2=	2.00
05-	2=	2.50
06-	2=	3.00
07-	2=	3.50
08-	2=	4.00
10-	2=	5.00
12-	2=	6.00
14-	2=	7.00
16-	2=	8.00

4-57 PSID

Cup	Spring	GPM
(1.1) 11-	4=	0.75
01-	4=	1.00
02-	4=	1.33
03-	4=	2.00
04-	4=	2.67
05-	4=	3.33
06-	4=	4.00
07-	4=	4.67
08-	4=	5.33
10-	4=	6.67
12-	4=	8.00
14-	4=	9.33
16-	4=	10.00

8-128 PSID

Cup	Spring	GPM
(1.1) 11-	8=	1.10
01-	8=	1.50
02-	8=	2.00
03-	8=	3.00
04-	8=	4.00
05-	8=	5.00
06-	8=	6.00
07-	8=	7.00
08-	8=	8.00
10-	8=	10.00
12-	8=	12.00
14-	8=	14.00
16-	8=	16.00

1-1/2" Standard Cartridge

1-14 PSID

Cup	Spring	GPM
09-	1=	3.00
10-	1=	3.33
12-	1=	4.00
14-	1=	4.67
16-	1=	5.33
18-	1=	6.00
20-	1=	6.67
22-	1=	7.33
24-	1=	8.00
26-	1=	8.67
28-	1=	9.33
30-	1=	10.00
32-	1=	10.67
34-	1=	11.33
36-	1=	12.00
38-	1=	12.67
40-	1=	13.33
42-	1=	14.00
44-	1=	14.67

2-32 PSID

Cup	Spring	GPM
09-	2=	4.50
10-	2=	5.00
12-	2=	6.00
14-	2=	7.00
16-	2=	8.00
18-	2=	9.00
20-	2=	10.00
22-	2=	11.00
24-	2=	12.00
26-	2=	13.00
28-	2=	14.00
30-	2=	15.00
32-	2=	16.00
34-	2=	17.00
36-	2=	18.00
38-	2=	19.00
40-	2=	20.00
42-	2=	21.00
44-	2=	22.00

4-57 PSID

Cup	Spring	GPM
09-	4=	6.00
10-	4=	6.67
12-	4=	8.00
14-	4=	9.33
16-	4=	10.67
18-	4=	12.00
20-	4=	13.33
22-	4=	14.67
24-	4=	16.00
26-	4=	17.33
28-	4=	18.67
30-	4=	20.00
32-	4=	21.33
34-	4=	22.67
36-	4=	24.00
38-	4=	25.33
40-	4=	26.67
42-	4=	28.00
44-	4=	29.33

8-128 PSID

Cup	Spring	GPM
09-	8=	9.00
10-	8=	10.00
12-	8=	12.00
14-	8=	14.00
16-	8=	16.00
18-	8=	18.00
20-	8=	20.00
22-	8=	22.00
24-	8=	24.00
26-	8=	26.00
28-	8=	28.00
30-	8=	30.00
32-	8=	32.00
34-	8=	34.00
36-	8=	36.00
38-	8=	38.00
40-	8=	40.00
42-	8=	42.00
44-	8=	44.00

Replaces form F-4355D

This specification © 2017 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606
(949) 559-6000 Fax (949) 559-6088
www.GriswoldControls.com

12/17
F-4355H



**Flow Control Cartridge Code
Quick Reference Guide**

2" Standard Cartridge

1-14 PSID		
Cup	Spring	GPM
36-	1=	12.00
42-	1=	14.00
48-	1=	16.00
54-	1=	18.00
60-	1=	20.00
66-	1=	22.00
72-	1=	24.00
78-	1=	26.00
84-	1=	28.00
90-	1=	30.00
96-	1=	32.00
102-	1=	34.00
108-	1=	36.00
114-	1=	38.00

2-32 PSID		
Cup	Spring	GPM
36-	2=	18.0
42-	2=	21.0
48-	2=	24.0
54-	2=	27.0
60-	2=	30.0
66-	2=	33.0
72-	2=	36.0
78-	2=	39.0
84-	2=	42.0
90-	2=	45.0
96-	2=	48.0
102-	2=	51.0
108-	2=	54.0
114-	2=	57.0

4-57 PSID		
Cup	Spring	GPM
36-	4=	24.0
42-	4=	28.0
48-	4=	32.0
54-	4=	36.0
60-	4=	40.0
66-	4=	44.0
72-	4=	48.0
78-	4=	52.0
84-	4=	56.0
90-	4=	60.0
96-	4=	64.0
102-	4=	68.0
108-	4=	72.0
114-	4=	76.0

8-128 PSID		
Cup	Spring	GPM
36-	8=	36.0
42-	8=	42.0
48-	8=	48.0
54-	8=	54.0
60-	8=	60.0
66-	8=	66.0
72-	8=	72.0
78-	8=	78.0
84-	8=	84.0
90-	8=	90.0
96-	8=	96.0
102-	8=	102.0
108-	8=	108.0
114-	8=	114.0

3" Standard Cartridge

1-14 PSID		
Cup	Spring	GPM
35-	1=	14.0
40-	1=	16.0
45-	1=	18.0
50-	1=	20.0
55-	1=	22.0
60-	1=	24.0
65-	1=	26.0
70-	1=	28.0
75-	1=	30.0
80-	1=	32.0
85-	1=	34.0
90-	1=	36.0
95-	1=	38.0
100-	1=	40.0
105-	1=	42.0
110-	1=	44.0
115-	1=	46.0
120-	1=	48.0
125-	1=	50.0
130-	1=	52.0
135-	1=	54.0
140-	1=	56.0
145-	1=	58.0
150-	1=	60.0
220-	1=	90.0
270-	1=	110.0
320-	1=	130.0

2-32 PSID		
Cup	Spring	GPM
35-	2=	17.5
40-	2=	20.0
45-	2=	22.5
50-	2=	25.0
55-	2=	27.5
60-	2=	30.0
65-	2=	32.5
70-	2=	35.0
75-	2=	37.5
80-	2=	40.0
85-	2=	42.5
90-	2=	45.0
95-	2=	47.5
100-	2=	50.0
105-	2=	52.5
110-	2=	55.0
115-	2=	57.5
120-	2=	60.0
125-	2=	62.5
130-	2=	65.0
135-	2=	67.5
140-	2=	70.0
145-	2=	72.5
150-	2=	75.0
220-	2=	110.0
270-	2=	135.0
320-	2=	160.0

4-57 PSID		
Cup	Spring	GPM
35-	4=	23.33
40-	4=	26.67
45-	4=	30.00
50-	4=	33.33
55-	4=	36.67
60-	4=	40.00
65-	4=	43.33
70-	4=	46.67
75-	4=	50.00
80-	4=	53.33
85-	4=	56.67
90-	4=	60.00
95-	4=	63.33
100-	4=	66.67
105-	4=	70.00
110-	4=	73.33
115-	4=	76.67
120-	4=	80.00
125-	4=	83.33
130-	4=	86.67
135-	4=	90.00
140-	4=	93.33
145-	4=	96.67
150-	4=	100.00
220-	4=	N/A
270-	4=	N/A
320-	4=	N/A

8-128 PSID		
Cup	Spring	GPM
35-	8=	35
40-	8=	40
45-	8=	45
50-	8=	50
55-	8=	55
60-	8=	60
65-	8=	65
70-	8=	70
75-	8=	75
80-	8=	80
85-	8=	85
90-	8=	90
95-	8=	95
100-	8=	100
105-	8=	105
110-	8=	110
115-	8=	115
120-	8=	120
125-	8=	125
130-	8=	130
135-	8=	135
140-	8=	140
145-	8=	145
150-	8=	150
220-	8=	N/A
270-	8=	N/A
320-	8=	N/A

3 – 18 PSID: 100 – 3 = 100.00 GPM

5 – 32 PSID: 135 – 5 = 135.00 GPM; 160 – 5 = 160.00 GPM; 200 – 5 = 200.00 GPM

7.5 – 32 PSID: 300 – 8 = 300.00 GPM

Replaces form F-4355D

This specification © 2017 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606
(949) 559-6000 Fax (949) 559-6088
www.GriswoldControls.com

12/17
F-4355H

