



SPECIFICATIONS:

- PSI/Temperature Rating:** 362 PSI / 275°F
- Cartridge:**
 - AISI Type 304 stainless steel
 - AISI Type 17-7 PH stainless steel spring
- Body Material:**
 - Ductile Iron ASTM A536-80
 - Class 60-40-18
- Retaining Clip**
 - AISI Type 302 stainless steel
- Body Tappings**
 - 1/4" NPT with P/T test valves
- End Connections:**
 - Groove Clamps are not supplied by Griswold

FLOW RATES (+/-5%)

SIZE	MODEL NO.	HEAD LOSS IN FEET ¹	PSID RANGE	GPM			HEAD LOSS IN FEET ¹	PSID RANGE	HIGHER FLOW RATES/ NO INCREMENTS
				MIN.	INCREMENT	MAX			
4"	AHU1PB	3.5	1-20	14.0	2.0	60	9.2	4-20	90, 110, 130
	AHU2PB	7.4	2-32	17.5	2.5	75	18.4	8-32	110, 135, 160
	AHU4PB	13.4	4-57	23.33	3.33	100	NONE		
	AHU8PB	30.0	8-128	35.0	5.0	150			

DIMENSIONS & WEIGHTS (NOMINAL)

SIZE	MODEL NO.	A LENGTH	B HEIGHT	C HEIGHT	D I.D.	WEIGHT (LBS.)
4"	AHU_PB	6.75	4.5	3.31	3.22	8.2

NOTES

¹ Head Loss in Feet is provided for pump head calculations. (1PSI = 2.307 Feet of Water)
 Replaces form F-3076B

This specification © 2005 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606
 (949) 559-6000 Fax (949) 559-6088
 www.GriswoldControls.com

12/05
 F-3076C



MODEL NUMBER SELECTION²

 A H U P B

Select a PSID control range
(1-1-20 or 4-20, 2=2-32 or 8-32,
4=4-57, 8=8-128, 0=No Cartridge)



NOTES

² Model no. and flow rate are indicated on label affixed to body.
Replaces form F-3076B

This specification © 2005 Griswold Controls

12/05
F-3076C

2803 Barranca Parkway, Irvine, CA 92606
(949) 559-6000 Fax (949) 559-6088
www.GriswoldControls.com

